UTAH OIL AND GAS CONSERVATION COMMISSION											
REMARKS	WELL LOG		CTRIC LOGS	X	WATER SANDS	LOCATI	ON INSPECTED		\$	UB REPORT/abd	
99/0	122	MPO	Ext to lo	7-20-	20001						
						· <u> </u>					
				•							
							-			-	
	-				·						
DATE FILED	-	NOVEMBE	R 19, 199	8							
LAND FEE &	PATENTED	STATE L	EASE NO		-	PUBLIC LEASE NO	UTI	U-6535	6	INDIAN	
DRILLING APP	PROVED	JANUARY	25, 1999	)							
SPUDDED IN											
COMPLETED			PUT TO PRODUC	CING							
INITIAL PROD	UCTION			-							
GRAVITY A P	I									<u></u> .	
GOR											
PRODUCING :	ZONES	•								<u></u>	
TOTAL DEPT	н			-							
WELL ELEVAT	TION										
DATE ABAND	ONED	5-30	-2000	LA		-		-	-		
FIELD		UNDESIG						-			••
UNIT											
COUNTY		UINTAH									
WELL NO	·	FED. L	44-31				AP	I NO.	43-04	7-33261	
LOCATION	623	FSL F	T FROM (N) (S) LINE	964 F	EL	FT FROM (E) (W)	LINE SE	SE		1/4 - 1/4 SEC	31
TWP	RGE	SEC	OPERATOR			TWP	RGE	SEC	OPERATOR		
	•					115	22E	31	LONE	MOUNTAIN	PROD.




Office (435) 789-0968 Cellular (435) 828-0968 350 S. 800 E. Vernal, UT 84078

September 16, 1998

Re: Well Fed L 44-31 SE/SE, Sec. 31, T11S, R22E Lease No. UTU-65356

Utah Division of Oil Gas and Mining 1594 West North Temple Suite 1210 P.O. Box 145801 Salt Lake City UT, 84114-5801



Dear Sirs:

Lone Mountain Production Company (Lone Mountain) respectfully requests a spacing exception for the subject well. The well was originally requested for the center of the SE ¼ of the SE ¼. The location was moved due to topographic considerations, and access conditions. The location was on sited with the BLM on September 15, 1998. Byran Tolman, from the BLM and Bill Ryan Agent for Lone Mountain were present. Both parties agreed with the site location.

The well is located 623' FSL, 964' FEL in Sec. 31, T11S, R22E.

A 460' radius circle around the proposed location in contained within Federal Lease UTU-65356.

If you have additional questions please contact me.

Sincerely

William (Bill) Ryan

Agent

(formerly 9-331c)

# TED STATES

IT OF THE INTERIOR 5. LEASE DESIGNATION AND SERIAL NO. **BUREAU OF LAND MANAGEMENT** UTU-65356 APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 1a TYPE OF WORK NA DRILL DEEPEN **PLUG BACK** 7. UNIT AGREEMENT NAME B TYPE OF WELL NA OII GAS SINGLE 8. FARM OR LEASE NAME WEL WELL OTHER ZONE MULTIPLE ZONE NA 2. NAME OF OPERATOR 9. WELL NO. **Lone Mountain Production Company** Fed. L 44-31 3. ADDRESS OF OPERATORS 10. FIELD OR LEASE NAME P.O. Box, 3394, Billings, MT. 59103 406-245-5077 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement) 629169-42 11. Sec., T., R., M., OR BLK 623' FSL, 964' FEL at surface SE/SE 4401127.16 AND SURVEY OR AREA 190 29H At proposed prod. Zone Sec. 31, T11S, R22E 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE 12. COUNTY OR PARISH [13. STATE 28.3 miles south of Ouray, Utah Uintah Utah 15. DISTANCE FROM PROPOSED LOC. TO NEAREST PROP. OR LEASE NO OF ACRES ASSIGNED LINE, FT. (Also to nearest drig. Unit line, if any) TO THIS WELL 623 925 40 16. DISTANCE FROM PROPOSED LOCATION 19. PROPOSED DEPTH 20. ROTARY OR CABLE TOOLS TO NEAREST WELL, DRILLING COMPLETED. NA' OR APPLIED FOR, ON THIS LEASE, FT. 6,000 Rotary 21. ELEVATION (SHOW WHETHER DF. RT, GR, etc.) 22. APPROX. DATE WORK WILL START 6,183' GR April 1, 1999 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH QUANTITY OF CEMENT 12 1/4 9 5/8 36 300 To Surface 7 7/8 4 1/2 11.6 T.D. Cement top to cover the oil shale Operator requests permission to drill the subject well. Please see the attached 10 Point and 13 Point Surface Use Plan. If you require additional information please contact: William Ryan 350 S., 800E. Vernal, Utah 435-789-0968 DIV. OF OIL, GAS & MINING IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposed in to deepen or plug back, give data on proposed productive zone and proposed new productive zone. If proposal is to drill or deepen directional, give pertinent data on subsurface location and measure and true vertical depths. Give blowout preventer program, if any William A Ryan SIGNATURE TITLE Agent Oct. 12, 1998 DATE ( This space for Federal or State Office use PERMIT NO. APPROVAL DATE BRADLEY G. HILL APPROVED BY TITLE CONDITIONS OF APPROVA

Faderal Approval of this Action is Necessary

\*See Instructions on Reverse Side

#### LONE MOUNTAIN PRODUCTION T11S, R22E, S.L.B.&M. Well location, FEDERAL #44-31, located as shown in the SE 1/4 SE 1/4 of Section 31, T11S, R22E, S.L.B.&M. Uintah County, S89'53'E - 77.76 (G.L.O.) Utah. BASIS OF FLEVATION SPOT ELEVATION LOCATED NEAR A LANDING STRIP IN THE NW 1/4 OF SECTION 9, T12S, R22E, S.L.B.&M. TAKEN (C.L.O.)LOT 1 FROM THE BUCK CAMP CANYON, QUADRANGLE, UTAH, UINTAH COUNTY, 7.5 MINUTE QUAD. (TOPOGRAPHIC MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 6337 FEET. N00.03'W LOT 2 0 (G.L. 1922 Brass Cap 1.0' High, Pile of Stones NORTH (Basis of Bearings, LOT 3 SCALE CERTIFICATE THIS IS TO CERTIFY THAT THE ABOVE PLATAMOR RECORDER FROM FIELD NOTES OF ACTUAL SURVEYS WIDE BY ME ON MINER MY SUPERVISION AND THAT THE SME ARE TRUE AND CORPORT TO THE 67.0 FEDERAL #44-31 BEST OF MY KNOWLEDGE AND Elev. Ungraded Ground = 6183' M, EO, OON LOT 4 UINTAH ENGINEERING & LAND SURVEYING N89\*57'W - 78.03 (G.L.O.) 1923 Brass Cap 1.3' High, Pile 85 SOUTH 200 EAST - VERNAL, UTAH 84078 of Stones (435) 789-1017 LEGEND: SCALE DATE SURVEYED: DATE DRAWN: 1" = 1000'08-07-98 08-07-98 LATITUDE = 39.48.42" = 90' SYMBOL PARTY REFERENCES = PROPOSED WELL HEAD. LONGITUDE = $109^{29}27$ " D.R.B. K.K. T.A. G.L.O. PLAT WEATHER FILE = SECTION CORNERS LOCATED. WARM LONE MOUNTAIN PRODUCTION

### **SELF-CERTIFICATION STATEMENT**

The following self-certification statement is provided per Federal requirements dated June 15, 1988.

Please be advised that Lone Mountain Prod., Co. are considered to be the operator of the following well.

Fed. L 44-31 NE 1/4, NE 1/4, Section 31, T. 11, R. 22 E. Lease UTU-65356 Uintah County, Utah

Lone Mountain Prod., Co. is responsible under the terms and conditions of the lease for the operations conducted upon the lease lands.

Federal bond coverage is provided by a state wide bond for the state of Utah. The bond is Fed. Ut-0719

William A. Ryan

Agent

**Rocky Mountain Consulting** 

350 S. 800 E.

Vernal UT 84078

435-789-0968 Office

435-828-0968 Cell

435-789-0970 Fax

# Ten Point Plan

Lone Mountain Prod., Co.

Fed. L 44-31 Surface Location SE 1/4, SE 1/4, Section 31, T. 11 S., R. 22 E.

#### 1. Surface Formation:

Green River

# 2. Estimated Formation Tops and Datum:

Formation Property of the Prop	<u>Depth</u>	<u>Datum</u>
Green River	Surface	+6,183' G.L.
Oil Shale	368	+5,815
Wasatch	2,843	+3,340
Mesaverda formation	4,593	+1,590
T.D.	6,000	+183

# 3. Producing Formation Depth:

Formation objective includes the Wasatch and its sub-members.

Off Set Well Information:

Off set well: None

### 4. Proposed Casing:

Hole	Casing	Grade	Setting	Casing	
<u>Size</u>	<u>Size</u>	Weight/Ft.	& Tread	<u>Depth</u>	New/Used
12 1/4	9 5/8	36	J-55/STC	300	New
7 7/8	4 1/2	11.6	J-55/LTC	T.D.	New

#### Cement Program:

Casing <u>Size</u>	Cement Type	Cement Amount	Cement Yield	Cement Weight
8 5/8	Class "G" 2% Calcium 1/4 #/sk. Cello Flake	200 sks. +/-	1.18 cu. ft./sk.	15.6 lbs./gal.
4 ½ Lead.	•			
	Class "G" 3% salt 16% gel (Bentonite) 10# sk Gilsonite .4 lbs./sk. FL 25	200 sks. +/-	3.90 cu. ft./sk.	11.0 lbs./gal.
Tail				

500 sks. +/-

.4 lbs/sk FL-25

# 5. BOP and Pressure Containment Data:

Class "G"

10% salt 10% Gypsum 2% WR14

The anticipated bottom hole pressure will be less than 3000 psi.

A 3000-psi WP BOP system as described in the BOP and Pressure Containment Data (attached) will be installed and maintained from the 9 5/8" surface casing. The BOP system including the casing will be pressure tested to the minimum standards set forth in "On Shore Order #2". The BOP will be mechanically checked daily during the drilling operation.

1.53 cu. ft./sk. 14.8 lbs./gal.

# 6. Mud Program:

Interval	Mud weight <u>lbs./gal.</u>	Viscosity Sec./Qt.	Fluid Loss Ml/30 Mins.	Mud Type
0-300	Air/Clear Water		No Control	Water/Gel
300-2500	Clear Water	****	No Control	Water/Gel
2500-T.D.	8.4-8.6	30	8-10	Water/Gel

### 7. Auxiliary Equipment:

Upper Kelly cock, full opening stabbing valve, 2 1/2" choke manifold and pit level indicator.

# 8. Testing, Coring, Sampling and Logging:

a) Test:

None are anticipated.

b) Cor

Coring:

There is the possibility of sidewall coring.

c) Sampling:

Every 10' from 2000' to T.D.

d)

Logging:

Type

Interval

DLL/SFL W/GR and SP

T.D. to Surf. Csg

FDC/CNL W/GR and CAL

T.D. to Surf. Csg

# 9. Abnormalities (including sour gas):

No abnormal pressures, temperatures or other hazards are anticipated. Oil and gas shows are anticipated in the Wasatch Formation. Other wells drilled in the area have not encountered over pressured zones or H2S.

#### 10. Drilling Schedule:

The anticipated starting date is April 1, 1999. Duration of operations expected to be 30 days.

# LONE MOUNTAIN PRODUCTION COMPANY

13 POINT SURFACE USE PLAN

FOR WELL

FED L 44-31

**LOCATED IN** 

SE 1/4, SE 1/4

SECTION 31, T. 11 S., R. 22 E., U.S.B.&M.

**UINTAH COUNTY, UTAH** 

**LEASE NUMBER: UTU-65356** 

SURFACE OWNERSHIP: FEDERAL

#### 1. Existing Roads

To reach the Lone Mountain Production Co. well Fed. L 44-31, in Section 31, T 11 S, R 22 E, from Ouray, Utah, proceed south on the paved and gravel road for 10 miles.

Turn east (left) on the Glen Bench road. Proceed 4 miles.

Stay to the east (right) on the Bitter Creek road. Proceed 6 miles.

Turn south (right) on the East Bench road. Proceed 9.4 miles.

Turn west (right) on the oil field access road. Proceed 1.3 miles to an existing Rosewood well # 5-6.

Turn north (left) at the entrance to the location. Proceed on the existing road .8 miles.

The proposed location will be at this point. All roads to this point are State or County Class D roads.

Please see the attached map for additional details.

#### 2. Planned access road

The proposed location will not require a new access road.

The last .8 mile of county road will have to upgraded. The up grade will be built to the following standards:

A) Approximate length	3,485 ft
B) Right of Way width	30 ft.
C) Running surface	18 ft.

D) Surfacing material	Native soil
E) Maximum grade	5%
F) Fence crossing	None
G) Culvert	None
H) Turnouts	None
I) Major cuts and fills	None
J) Road flagged	Yes
K)Access road surface owner	rship
	Federal
L) All new construction on le	ease

Yes

M) Pipe line crossing

None

Please see the attached location plat for additional details.

A BLM right of way will not be required. All construction will be on lease.

#### 3. Location of existing wells

The following wells are located within a one mile radius of the location site.

A) Producing well	None
B) Water well	None
C) Abandoned well	None
D) Temp. abandoned well	None
E) Disposal well	None
F) Drilling/Permitted well	

Rosewood Fed. 5-6 Sec. 5, T12S, R22E

G) Shut in wells

H) Injection well

None

None

None

I) Monitoring or observation well

None

Please see the attached map for additional details.

# 4. Location of tank batteries, production facilities, and production gathering service lines.

All production facilities are to be contained within the proposed location site. Please see the attached plat plan for a typical gas well separator installation and well site piping.

All permanent (on site for more than six months or longer) structures constructed or installed will be painted a **Juniper Green** color. Facilities required to comply with O.S.H.A. (Occupational Safety and Health Act) will be excluded. The required **paint** color is **Juniper Green**.

All tanks will be surrounded by a dike of sufficient capacity to contain the storage capacity of the largest tank in the battery. The integrity of the dike will be maintained.

The operator will adhere to all site security guidelines and regulations identified in 43 cfr 3126.7.

All off lease storage, off lease measurement, commingling on lease or off lease, of production, will have prior written approval from the authorized officer.

If the well is capable of production in paying quantities a surface pipeline will be required. The line will be welded on location and pulled to the tie in point. The line will then be boomed off the road. The approximate length will be 2,100 ft. The right of way width will be 15 feet.

The gathering pipeline will be a 4" steel surface pipeline.

Please see the attached location diagram for pipeline location. There will be no additional surface disturbances required for the installation of a gathering line.

The gas meter run will be located within 500' of the well head. The gas line will be buried or anchored down from the well head to the meter. Meter runs will be housed and/or fenced.

The gas meter will be calibrated and the tank strapped in place prior to any deliveries. Tests for meter accuracy will be conducted monthly for the first three months on new meter installations and at least quarterly thereafter. The authorized officer will be provided with a date and time for the initial meter calibration and all future meter proving schedule. A copy of the meter calibration report will be submitted to the BLM Vernal District Office, Vernal Utah. All measurement facilities will conform to API (American Petroleum Institute) and AGA (American Gas Association) standards for gas and liquid hydrocarbon measurement.

# 5. Location and type of water supply #See Update 1-19-99 #49-1547 Water for drilling and cementing the

Water for drilling and cementing the subject well will be hauled by truck from Bitter Creek at the bottom of Camp Canyon. Water for completion will come from the listed location or Vernal City.

#### 6. Source of construction materials

All construction material for this location site and access road shall be borrow material accumulated during construction of the location site and access road. Additional road gravels or pit lining material will be obtained from private sources.

#### 7. Methods for handling waste disposal

#### A) Pit construction and liners:

The reserve pit will be approximately 10 ft. deep and most of the depth shall be below the surface of the existing ground. Please see the attached plat for details.

The reserve pit will be lined if the pit is blasted or soil conditions found at the time the location is constructed indicates the need for a pit liner.

The reserve pit will not be used to store water for drilling. A semi-closed system will be used to drill the well. All fresh water for drilling will come from a frac tank placed on location and from the rig tank. The pit will be used to hold non-flammable materials such as cuttings, salt, drilling fluids, chemicals, produced fluids, etc.

#### B) Produced fluids:

Produced water will be confined to the reserve pit, or if deemed necessary, a storage tank for a period not to exceed 90 days after initial production. During the 90 days an application will be made to the authorized officer for approval of a permanent disposal method and location.

#### C) Garbage:

A trash cage fabricated from expanded metal will be used to hold trash on location and will be removed to an authorized land fill location.

## D) Sewage:

A portable chemical toilet will be supplied for human waste.

#### E) Site clean up:

After the rig is moved off the location the well site area will be cleaned and all refuse removed.

#### 8. Ancillary facilities

There are no ancillary facilities planned at this time and none are foreseen for the future.

#### 9. Well-site layout

Location dimensions are as follow:

A) Pad length	325 ft.
B) Pad width	155 ft.
C) Pit depth	10 ft.
D) Pit length	180 ft.
E) Pit width	50 ft.
F) Max cut	6.5 ft.
G) Max fill	5.2 ft.
H) Total cut yd's	6,200 cu. yd's
I) Pit location	west side
J) Top soil location	west side
K) Access road location	
	south end
L) Flare pit	corner R

Please see the attached location diagram for additional details.

All pits will be fenced according to the following minimum standards:

A) Thirty nine inch net wire shall be used with at least one strand of wire on top of the net wire. Barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence.

- B) The net wire shall be no more than 2 inches above the ground. The barbed wire shall be 3 inches above the net wire. Total height of the fence shall be at least 42 inches.
- C) Corner posts shall be cemented and/or braced in such a manner to keep the fence tight at all times.
- D) Standard steel, wood or pipe posts shall be used between the corner braces.

  Maximum distance between any two posts shall be no greater than 16 ft.
- E) All wire shall be stretched by using a stretching device before it is attached to the corner posts.

#### 10. Plans for restoration of the surface

Prior to construction of the location, the top 6 inches of soil material will be stripped off the location and the pit area. The topsoil removed and piled will amount to approximately 1,000 cubic yards of material. Topsoil will be stockpiled in two distinct piles (location topsoil and pit topsoil). Placement of the topsoil is noted on the attached location plat. The topsoil pile from the location will be seeded as soon as the soil is stock piled with the seed mix listed below. The seeded area will be walked over with a cat after the seed has been broad cast. The unused portion of the location (the area outside the dead men.) will be recontoured

The dirt contractor will be provided with an approved copy of the surface use plan prior to construction activities.

Changes to the drainage during the construction activities shall be restored to its original line of flow or as near as possible when the pit is back-filled

All disturbed areas will be recontoured to the approximate natural contours. Prior to back filling the pit the fences around the reserve pit will be removed.

The reserve pit will be reclaimed within 90 days of well completion. If the reserve pit has not dried sufficiently to allow back filling, an extension on the time requirement for back filling the pit will be requested. Once reclamation activities have begun, they shall be completed within 30 days.

After the reserve pit has been reclaimed, no depressions in the soil covering the reserve pit will be allowed. The objective is to keep seasonal rainfall and run off from seeping into the soil used to cover the reserve pit. Diversion ditches and water bars will be used to divert run off as needed.

When restoration activities have been completed, the location site and new access road cuts and shoulders shall be reseeded. Prior to reseeding, all disturbed areas will be scarified and left with a rough surface.

After the seed has been broad cast the area seeded will be walked with the cat.

A) Seeding dates:

Seed will be spread when the topsoil is stock piled and when reclamation work is performed.

#### C) Seed Mix

Black Sage 2#/acre

Needle and thread 3#/acre

Shad Scale 4#/acre
(Antriplex Cenfertifolia)

**Indian Rice Grass** 

3#/acre

At such time as the well is plugged and abandoned the operator will submit a surface reclamation plan to the surface management agency for prescribed seed mixture and reseeding requirements.

#### 11. Surface ownership:

Access road

Federal

Location

**Federal** 

**Pipeline** 

Federal

#### 12. Other information

#### A) Vegetation:

The vegetation coverage is slight. The majority of the existing vegetation consists of sagebrush. Rabbit brush, bitter brush and Indian rice grass are also found on the location.

## B) Dwellings:

There are no dwellings or other facilities within a one mile radius of the location.

# C) Archeology:

The location has not been surveyed. A copy of that survey will be forwarded to your office.

If, during operations, any archaeological or historical sites, or any objects of antiquity (subject to the antiquities act of June 8, 1906) are discovered, all operations which would effect such sites will be suspended and the discovery reported promptly to the surface management agency.

#### D) Water:

The nearest water is Bitter Creek located 4 miles to the east.

#### E) Chemicals:

No pesticides, herbicides or other possible hazardous chemicals will be used without prior application.

#### F) Notification:

#### a) Location construction

At least forty eight (48) hours prior to construction of location and access roads

#### b) Location completion

Prior to moving in the drilling rig.

#### c) Spud notice

At least twenty-four (24) hours prior to spudding the well.

### d) Casing string and cementing

At least twenty-four (24) hours prior to running casing and cementing all casing strings.

# e) BOP and related equipment tests At least twenty-four (24) hours prior

to initial pressure tests.

#### f) First production notice

Within five (5) business days after the new well begins, or production resumes after well has been off production for more than ninety 90 days.

#### H) Flare pit:

The flare pit will be located in corner B of the reserve pit out side the pit fence and 100 feet from the bore hole on the west side of the location. All fluids will be removed from the pit within 48 hours of occurrence.

#### Lessees or Operator's representative and certification

#### A) Representative

William A. Ryan

**Rocky Mountain Consulting** 350 South 800 East Vernal, Utah 84078

Office

435-789-0968

Fax

435-789-0970

Cellular

435-828-0968

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, onshore oil and gas orders, the applicable laws, regulations, and any applicable notices to lessees. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished to the field representative to ensure compliance.

This drilling permit will be valid for a period of one year from the date of approval. After permit termination, a new application will be filed for approval for any future operations.

#### B) Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill-site and access route, that I am familiar with the conditions which presently exist, that the statements made in this plan are, to the best of my knowledge and belief, true and correct, and that the work associated with the operation proposed herein will be performed by Lone Mountain Production Company and its contractors and subcontractors in

conformity with this plan and terms and conditions with this plan and the terms and conditions under which it is approved.

Date On 12 178
William a Tyon

William A. Ryan, Agent **Rocky Mountain Consulting** 

#### Statement of use of Hazardous Material

No chemical(s) from the EPA's Consolidated list of <u>Chemicals subject to Reporting Under Title III of the Superfund Amendments and Reauthorization, Act (SARA) of 1986.</u> will be used, produced, transported, stored, disposed, or associated with the proposed action, No extremely hazardous substances, as defined in 40 cfr 355, will be used, produced, stored, transported, disposed, or associated with the proposed action.

If you require additional information please contact:

William A Ryan Agent for Lone Mountain Production Co. Rocky Mountain Consulting 350 S. 800 E. Vernal Utah, 84078

Telephone (801) 789-0968 office (801) 823-6152 cellular (801) 789-0970 fax LONE MOUNTAIN
TYPICAL
GAS WELL

Well HEAD


Walve & check


TO GAS SALES


Water dump line


Valve & check


Valve & check














APD RECEIVED: 11/19/98	API NO. ASSIGNED: 43-047-33261
WELL NAME: FED L 44-31 OPERATOR: LONE MOUNTAIN PROD CO CONTACT: Bill Ryan (435) 789-0968	(N7210)
PROPOSED LOCATION:  SESE 31 - T11S - R22E  SURFACE: 0623-FSL-0964-FEL  BOTTOM: 0623-FSL-0964-FEL  UINTAH COUNTY  UNDESIGNATED FIELD (002)  LEASE TYPE: FED  LEASE NUMBER: UTU-65356  SURFACE OWNER: Federal  PROPOSED FORMATION: WSTC	INSPECT LOCATION BY: / / TECH REVIEW Initials Date Engineering Geology Surface
RECEIVED AND/OR REVIEWED:  Plat Bond: Federal M State[] Fee[] (No. WT-07/9) Potash (Y/N) N Oil Shale (Y/N) *190-5(B) Water Permit (No. 49-/547) RDCC Review (Y/N) (Date: )  NA Fee Surf Agreement (Y/N)	LOCATION AND SITING:  R649-2-3. Unit R649-3-2. General R649-3-3. Exception Drilling Unit Board Cause No: Date:
COMMENTS: * * Need add' 1 Lo. " Excep  * BLM / Vernal aprv. 1-14  STIPULATIONS: (1) FEDERAL APPROC	



OPERATOR: LONE MOUNTAIN (N7210)

FIELD: UNDESIGNATED (002)

SEC. 31 TWP 11S, RNG 22E

COUNTY: UINTAH UNIT: NONE

25		30		29
35 T11S R2	E T11S R22E	31 <b>⊙</b> FEDERA	L L 44-31	32
T12S R2	E T12S R22E	BUCK CANY	ON FIELD	S  GOVERNMENT#1-5




Office (435) 789-0968 Cellular (435) 828-0968

350 S. 800 E. Vernal, UT 84078

January 19, 1999

Re: Water for Drilling

Utah Division of Oil Gas and Mining 1594 West North Temple Suite 1210 P.O. Box 145801 Salt Lake City UT, 84114-5801 Lisha Cordova



#### Dear Lisha:

Lone Mountain Production Company (Lone Mountain) would like to change the point of diversion for water requested in five APD submitted to your office recently. The water will be used for drilling and completion operations.

The five locations are the:

State L 31-16, Sec. 16, T11S, R22E Fed. L 43-26, Sec. 26, T11S, R22E Fed. L 44-31, Sec. 31, T11S, R22E Fed. R 42-11, Sec. 11, T12S,R22E Fed. R 42-8, Sec. 8, T12S, R22E

The new water source will be the Rose Wood water plant, Well 5a in Sec. 13, T11S, R24E water permit number 49-1547.

Sincerely

William (Bill) Ryan Agent



Michael O Leavitt
Governor

Ted Stewart
Executive Director
Lowell P Braxton
Division Director

1594 West North Temple, Suite 1210 PO Box 145801 Salt Lake City, Utah 84114-5801 801-538-5340 801-359-3940 (Fax)

801-538-7223 (TDD)

January 25, 1999

Lone Mountain Production Company P.O. Box 3394 Billings, Montana 59103

Re: Fed. L 44-31 Well, 623' FSL, 964' FEL, SE SE, Sec.31, T.11 S., R. 22 E.,

Uintah County, Utah

#### Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

Appropriate information has been submitted to DOGM by the operator and administrative approval of the requested exception location is hereby granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-33261.

Sincerely,

Jøhn R. Baza

Associate Director

lwp

**Enclosures** 

cc: Uintah County Assessor

Bureau of Land Management, Vernal District Office

Operator:	Lone Mo	<u>ountain F</u>	roduction	on Com	pany				
Well Name & Number: _		Fed. L 4	4-31						
API Number:		43-047-3	33261			<u> </u>			
Lease:	Federal	<del></del>	Surfac	e Owne	r:	Federal			_
Location:	SE SE		Sec	31	_ T	11 S.	_ R	22 E.	

#### **Conditions of Approval**

#### 1. General

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for Permit to Drill.

#### 2. Notification Requirements

Notify the Division within 24 hours of spudding the well. Contact Carol Daniels at (801)538-5284.

Notify the Division prior to commencing operations to plug and abandon the well. Contact Dan Jarvis at (801) 538-5338 or Robert Krueger at (801) 538-5274.

#### 3. Reporting Requirements

All required reports, forms and submittals shall be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

4. State approval of this well does not supersede the required federal approval which must be obtained prior to drilling.

DEPARTMENT OF THE INTERIOR

|--|

5. LEASE DESIGNATION AND SERIAL NO. UTU-65356

ADDI ICATI	ON FOR PER	MIT TO D	RILL D	EEPEN. OR	PLUG	BACK	6. IF INDIAN. A	LLOTTEE O	R TRIBE NAME
a TYPE OF WORK	OIL OIL MIL							NA	
DRILL TYPE OF WELL	_ 🗶	DEEPEN		PLUG BA	CK [		7. UNIT AGRE	EMENT NAM	IE.
وسسمو	GAS 🗍		SING	GLE [	Ī		8. FARM OR L		
WELL W	ELL X	THER	zo	NE MULTIPLE ZONE		X		NA	
NAME OF OPERATOR	Mountain Prod	uction Co	mpany				9. WELL NO.	Fed. L	44-31
B. ADDRESS OF OPERATO						<del>,, ,, ,, ,, ,,,,,,,,,,,,,,,,,,,,,,,,,</del>	10. FIELD OR	LEASE NAM	E
	ox, 3394, Billir	ngs, MT. 5	9103 4	406-245-5077					
LOCATION OF WELL (Re							11. Sec., T., R		K
at surface	623° FSI	., 964' FEL	-	SE/SE			AND SURVEY		S, R22E
At proposed prod. Zone  4. DISTANCE IN MILES AF	ND DIRECTION FROM NEA	REST TOWN OR	POST OFFICE	10 117		2/1	12. COUNTY		
	28.3 mile	s south of	Ouray, U	Itah 430.47	33	061	Uintah		Utah
		PROP. OR LEAS	E 16. NO. OF	ACRES IN LEASE		17. NO. OF AC		D	
JNE , FT. (Also to nearest o	ang. Orm. mio, n eny)	623'		925	'		40		
6. DISTANCE FROM PRO			19. PROPO	OSED DEPTH		20. ROTARY O	R CABLE TOO	LS	
TO NEAREST WELL, DRILL OR APPLIED FOR, ON THI		NA'	1	6,000'			Rotary		
	HETHER DF. RT, GR, etc.)						22. APPROX.		K WILL START 1, 1999
		6,183' GF		ID OFFICE SPACE	2016		J	Vhiii	1, 1000
SIZE OF HOLE	SIZE OF CASING	PROPOSED (		ND CEMENT PROGI	RAM	QUANTIT	Y OF CEMEN	f	
12 1/4	9 5/8		36	300		To Sı	ırface		
7 7/8	4 1/2	11	.6	T.D.			ent top to il shale	cover	
£.	If you require	additional i	nformati	on please cont	act:				
	ii you lequile	MARITALIE I	, <del>.,,</del> ,,,,,,,	p.3400 00114		AT A F	• • • • • •	• • • • • • • • • • • • • • • • • • • •	ارس. م
	William Ryan		居の	BINE	21	<b>5</b>		.*	fi 
	350 S., 800E.	IIU)			M	~ /		رة: جدورون	an de
	Vernal, Utah					Ų	OT 15	<b>353</b>	
	435-789-0968		APR	1 9 1999	ツ	BLM V	EMNAL	UTA	1
	100 100 0000	"		1	1			·, 😎 • i i i i	•
		יות	DE AII	GAS & MINI	NG				
IN ABOVE SPACE DESC	RIBE PROPOSED PROGRA	am: It drodesed in t	o deeben us bit		<del>sea prouu</del> c	tive zone and po			
blowout preventer program		Unai, give pertinent	Jaia Oli SUUSUI	THE POSSION AND INDUSTRE	and 40				
24	(1),00.	LE TI	u -						
SIGNATURE	William A F	Ryan	TITL	E Agent			DATE	Oct.	12, 1998
	Federal of State Unice use)								
(		•	man.	DITIONS		FAPI	POR		ATTACH
PERMIT NO.	1/M	2//					8 8 CF 6		4 6 4000
APPROVED BY	67/2/2/12/	Spaining	D TITL	Assistant F		-	DATE	JAN	1 5 1999
CONDITIONS OF APPRO	VAL, IF ANY:	XICI III		- Mineral F	lesoun	CES		-KA	4) Boner
								17.0	W receip 2/8/99
		*Cool-ot	uetiene e	n Davana Sida					2/6/11
		"See instri	uctions of	n Reverse Side					

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

COAs Page 1 of 8 Well No.: Federal L 44-31

# CONDITIONS OF APPROVAL APPLICATION FOR PERMIT TO DRILL

Company/Operator: Lone Mountain Production Company	
Well Name & Number: Federal L 44-31	
API Number: <u>43-047-33261</u>	
Lease Number: U - 65356	
Location: SESE Sec. 31 T.11S R. 22E	

#### **NOTIFICATION REQUIREMENTS**

Location Construction

at least forty-eight (48) hours prior to construction of

location and access roads.

**Location Completion** 

prior to moving on the drilling rig.

Spud Notice

at least twenty-four (24) hours prior to spudding the well.

Casing String and Cementing

at least twenty-four (24) hours prior to running casing and cementing all casing strings.

BOP and Related Equipment Tests

at least twenty-four (24) hours prior to initiating pressure

tests.

First Production

Notice

within five (5) business days after new well begins, or production resumes after well has been off production for

more than ninety (90) days.

For more specific details on notification requirements, please check the Conditions of Approval for Notice to Drill and Surface Use Program.

COAs Page 2 of 8 Well No.: Federal L 44-31

# CONDITIONS OF APPROVAL FOR NOTICE TO DRILL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with applicable laws, regulations (43 CFR 3100), Onshore Oil and Gas Orders, and the approved plan of operations. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished the field representative to insure compliance.

Be aware fire restrictions may be in effect when location is being constructed and/or when well is being drilled. Contact the appropriate Surface Management Agency for information.

#### A. <u>DRILLING PROGRAM</u>

# 1. <u>Estimated Depth at Which Oil, Gas, Water, or Other Mineral Bearing Zones are Expected to be Encountered</u>

Report <u>ALL</u> water shows and water-bearing sands to Tim Ingwell of this office **prior to setting the next casing or requesting plugging orders**. Faxed copies of State of Utah form OGC-8-X are acceptable. If noticeable water flows are detected, submit samples to this office along with any water analyses conducted.

All usable water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling, will be recorded by depth and adequately protected. All oil and gas shows will be tested to determine commercial potential.

# 2. <u>Pressure Control Equipment</u>

The BOP and related equipment shall meet the minimum requirements of Onshore Oil and Gas Order No. 2 for equipment and testing requirements, procedures, etc., for a <a href="Mailto:3M">3M</a> system and individual components shall be operable as designed. Chart recorders shall be used for all pressure tests.

Test charts, with individual test results identified, shall be maintained on location while drilling and shall be made available to a BLM representative upon request.

If an air compressor is on location and is being utilized to provide air for the drilling medium while drilling, the special drilling requirements in Onshore Oil and Gas Order No. 2, regarding air or gas drilling shall be adhered to. If a mist system is being utilized then the requirement for a deduster shall be waived.

COAs Page 3 of 8 Well No.: Federal L 44-31

# 3. Casing Program and Auxiliary Equipment

Surface casing shall have centralizers on the bottom three joints, with a minimum of one centralizer per joint.

As a minimum, the usable water and oil shale resources shall be isolated and/or protected by having a cement top for the production casing at least 200 ft. above the top of the Mahogany Oil Shale, identified at  $\pm 1,122$  ft. If gilsonite is encountered while drilling, it shall be isolated and/or protected via the cementing program.

# 4. Mud Program and Circulating Medium

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

No chromate additives will be used in the mud system on Federal and Indian lands without prior BLM approval to ensure adequate protection of fresh water aquifers.

# 5 .Coring, Logging and Testing Program

Daily drilling and completion progress reports shall be submitted to this office on a weekly basis.

All Drill Stem tests (DST) shall be accomplished during daylight hours, unless specific approval to start during other hours is obtained from the AO. However, DSTs may be allowed to continue at night if the test was initiated during daylight hours and the rate of flow is stabilized and if adequate lighting is available (i.e., lighting which is adequate for visibility and vaporproof for safe operations). Packers can be released, but tripping should not begin before daylight unless prior approval is obtained from the AO.

A cement bond log (CBL) will be run from the production casing shoe to the top of the cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.

Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (Form 3160-4) will be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3164. Two copies of all logs, core descriptions, core analyses, well-test data, geologic summaries, sample description, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, will be filed with Form 3160-4. Samples (cuttings, fluids, and/or gases) will be submitted when requested by the AO.

COAs Page 4 of 8 Well No.: Federal L 44-31

#### 6. Notifications of Operations

No location will be constructed or moved, no well will be plugged, and no drilling or workover equipment will be removed from a well to be placed in a suspended status without prior approval of the AO. If operations are to be suspended, prior approval of the AO will be obtained and notification given before resumption of operations.

Operator shall report production data to MMS pursuant to 30 CFR 216.5 using form MMS/3160.

<u>Immediate Report</u>: Spills, blowouts, fires, leaks, accidents, or any other unusual occurrences shall be promptly reported in accordance with the requirements of NTL-3A or its revision.

If a replacement rig is contemplated for completion operations, a "Sundry Notice" (Form 3160-5) to that effect will be filed, for prior approval of the AO, and all conditions of this approved plan are applicable during all operations conducted with the replacement rig.

The date on which production is commenced or resumed will be construed for oil wells as the date on which liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which liquid hydrocarbons are first produced into a permanent storage facility, whichever first occurs; and, for gas wells as the date on which associated liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which gas is first measured through permanent metering facilities, whichever first occurs.

Should the well be successfully completed for production, the AO will be notified when the well is placed in a producing status. Such notification will be sent by telegram or other written communication, not later than five (5) days following the date on which the well is placed on production.

Gas produced from this well may not be vented or flared beyond an initial authorized test period of 30 days or 50 MMCF following its completion, whichever occurs first, without the prior written approval of the Authorized Officer. Should gas be vented or flared without approval beyond the authorized test period, the operator may be directed to shut-in the well until the gas can be captured or approval to continue venting or flaring as uneconomic is granted and the operator shall be required to compensate the lessor for that portion of the gas vented or flared without approval which is determined to have been avoidably lost.

COAs Page 5 of 8 Well No.: Federal L 44-31

A schematic facilities diagram as required by 43 CFR 3162.7-5(d) shall be submitted to the appropriate Field Office within 60 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with 43 CFR 3162.7-5 (1).

No well abandonment operations will be commenced without the prior approval of the AO. In the case of newly drilled dry holes or failures, and in emergency situations, oral approval will be obtained from the AO. A "Subsequent Report of Abandonment" Form 3160-5, will be filed with the AO within thirty (30) days following completion of the well for abandonment. This report will indicate where plugs were placed and the current status of surface restoration. Final abandonment will not be approved until the surface reclamation work required by the approved APD or approved abandonment notice has been completed to the satisfaction of the AO or his representative, or the appropriate Surface Managing Agency.

#### 7. Other Information

All loading lines will be placed inside the berm surrounding the tank battery.

All off-lease storage, off-lease measurement, or commingling onlease or off-lease will have prior written approval from the AO.

The oil and gas measurement facilities will be installed on the well location. The oil and gas meters will be calibrated in place prior to any deliveries. Tests for meter accuracy will be conducted on initial meter installations and at least quarterly thereafter. The AO will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports will be submitted to the Vernal District Office. All meter measurement facilities will conform with Onshore Oil & Gas Order No. 4 for liquid hydrocarbons and Onshore Oil & Gas Order No. 5 for natural gas measurement.

The use of materials under BLM jurisdiction will conform to 43 CFR 3610.2-3.

There will be no deviation from the proposed drilling and/or workover program without prior approval from the AO. Safe drilling and operating practices must be observed. All wells, whether drilling, producing, suspended, or abandoned will be identified in accordance with 43 CFR 3162.

"Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.3-2.

COAs Page 6 of 8 Well No.: Federal L 44-31

Section 102(b)(3) of the Federal Oil and Gas Royalty Management Act of 1982, as implemented by the applicable provisions of the operating regulations at Title 43 CFR 3162.4-1(c), requires that "not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160-5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed."

If you fail to comply with this requirement in the manner and time allowed, you shall be liable for a civil penalty of up to \$10,000 per violation for each day such violation continues, not to exceed a maximum of 20 days. See Section 109(c)(3) of the Federal Oil and Gas Royalty Management Act of 1982 and the implementing regulations at Title 43 CFR 3162.4-1(b)(5)(ii).

The APD approval is for a period of one (1) year from the signature date. An extension period may be granted, if requested, prior to the expiration of the original approval period.

In the event after-hours approvals are necessary, please contact one of the following individuals:

Ed Forsman

(435) 789-7077

Petroleum Engineer

Wayne P. Bankert

(435) 789-4170

Petroleum Engineer

(435) 781-1190

Jerry Kenczka Petroleum Engineer

BLM FAX Machine (435

(435) 781-4410

COAs Page 7 of 8 Well No.: Federal L 44-31

# EPA'S LIST OF NONEXEMPT EXPLORATION AND PRODUCTION WASTES

While the following wastes are nonexempt, they are not necessarily hazardous.

Unused fracturing fluids or acids

Gas plant cooling tower cleaning wastes

Painting wastes

Oil and gas service company wastes, such as empty drums, drum rinsate, vacuum truck rinsate, sandblast media, painting wastes, spend solvents, spilled chemicals, and waste acids

Vacuum truck and drum rinsate from trucks and drums, transporting or containing nonexempt waste

Refinery wastes

Liquid and solid wastes generated by crude oil and tank bottom reclaimers

Used equipment lubrication oils

Waste compressor oil, filters, and blowdown

Used hydraulic fluids

Waste solvents

Waste in transportation pipeline-related pits

Caustic or acid cleaners

Boiler cleaning wastes

Boiler refractory bricks

Incinerator ash

Laboratory wastes

Sanitary wastes

Pesticide wastes

Radioactive tracer wastes

Drums, insulation and miscellaneous solids.

COAs Page 8 of 8 Well No.: Federal L 44-31

# **SURFACE USE PROGRAM Conditions of Approval (COAs)**

-Access roads and surface disturbing activities will conform to standards outlined in the Bureau of Land Management and Forest Service publication: <u>Surface Operating Standards for Oil and Gas Exploration and Development</u>, (1989).

The road shall be constructed/upgraded to meet the standards of the anticipated traffic flow and all-weather road requirements. Construction/upgrading shall include ditching, draining, and crowning (2 to 3%). Graveling or capping the roadbed will be required as necessary to provide a well constructed safe road. Prior to construction/upgrading, the proposed road surface or existing road shall be cleared of any snow cover and allowed to dry completely. Traveling off the 30 foot right-of-way will not be allowed. Should mud holes develop, they shall be filled in to prevent detours. Road drainage crossings shall be of the typical dry creek drainage crossing type. Crossings shall be designed so they will not cause siltation or accumulation of debris in the drainage crossing nor shall the drainages be blocked by the roadbed. Erosion of drainage ditches by runoff water shall be prevented by diverting water off at frequent intervals by means of cutouts. Upgrading shall not be allowed during muddy conditions. When snow is removed from the road during the winter months, the snow shall be pushed outside of the burrow ditches and the turn outs shall be kept clear so that when the snow melts the water will be channeled away from the road.

- -The operator will control noxious weeds along rights-of-way for roads, pipelines, well sites, or other applicable facilities. A list of noxious weeds may be obtained from the BLM, or the appropriate County Extension Office. On BLM administered land it is required that a Pesticide Use Proposal shall be submitted, and given approval, prior to the application of herbicides or other pesticides or possible hazardous chemicals.
- -Drilling rigs and/or equipment used during drilling operations on this well site will not be stacked or stored on Federal Lands after the conclusion of drilling operations or at any other time without BLM authorization. However, if BLM authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities. (The BLM does not seek to compete with private industry. There are commercial facilities available for stacking and storing drilling rigs)

Form 3160-5 (June 1990)

# **UNITED STATES** DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE\* (Other Instructions on reverse side)

Form Approved. Budget Bureau No. 1004-0135

Expires: March 31, 1993

BUREAU OF L	AND MANAGEMENT	5. LEASE DESIGNATION AND SERIAL NO. UTU-65356
SUNDRY NOTICE	S AND REPORTS ON WELLS	6. IF INDIAN, ALLOTEE OR TRIBE NAME
	drill or to deepen or reentry to a different reservoir.	
	FOR PERMIT—* for such proposals	7. IF UNIT OR CA. AGREEMENT DESIGNATION
SUBMI	T IN TRIPLICATE	7. IF UNIT OR CA, AGREEMENT DESIGNATION
b. TYPE OF WELL		
OIL GAS	SINGLE MULTIPLE	8. WELL NAME and No.
WELL OTHER	ZONE ZONE	Federal No. L 44-31
2. NAME OF OPERATOR		9. API WELL NO.
Lone Mountain Production Compar	ly	43-047-33261
3. ADDRESS OF OPERATOR	0103	10. Field and Pool, or Exploratory Area
P. O. Box 3394, Billings, Montana 5		
4. LOCATION OF WELL (Footage, Sec. T., R., M., or Survey De	• •	11. County or Parish, State
623' FSL, 964' FEL Section 31-T11S	-R22E	Uintah County, Utah
(SENW)		
12. CHECK APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF AC	TION
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Pługging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other APD Extension	Dispose of Water
		(Note: Report results of multiple completion on Well
		Completion or Recompletion Report and Log Form)

13. Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If a well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Lone Mountain Production Company, as operator for White River Resource Management Inc., requests the extension of one year on the approved APD for the subject well.

If additional information is needed please contact the following agent:

Approved by the Utah Division of Oil, Gas and Mining Date: 12/20/99 By:	William Ryan Rocky Mountain Consulting  Phone: (435) 789-0968  COPY SENT TO OPERAGE Date: 12-22-91 Initials: CHP	RECEIVED  DEC 1 5 1999  DIVISION OF OIL, GAS & MINING
14. I hereby certify that the foregoing is true and correct.	The state of the s	
Signed: Man & Pontin	Title: President	Date: December 15, 1999
(This space for Federal or State office use)		
APPROVED BY: CONDITIONS OF APPROVAL IF ANY	TITLE:	DATE:
Title 18 U.S.C. Section 1001, make it a crime for any	person knowingly and willfully to make any d	lepartment or agency of the United States any



# United States Department of the Interior

#### **BUREAU OF LAND MANAGEMENT**

Vernal Field Office 170 South 500 East Vernal, Utah 84078-2799 http://www.blm.gov/utah/vernal

Phone: (435) 781-4400 Fax: (435) 781-4410

IN REPLY REFER TO: 3160 UT08300

May 23, 2000

Lone Mountain Production Company P. O. Box 3394 Billings, MT 59103

Re:

**Notification of Termination** Well No. Federal L 44-31 SESE, Section 31, T11S, R22E Lease No. UTU-65356

Uintah County, Utah 43-047-33261

Gentlemen:

The Application for Permit to Drill the above-referenced well was approved on February 8, 1999.

According to our records, Lease No. UTU-65356 expired as of September 30, 1999. In view of the foregoing, this office is notifying you the approval of the referenced application and the request for extension have both terminated.

This office requires a letter confirming that no surface disturbance has been made for this drill site. Any surface disturbance associated with the approved location of this well is to be rehabilitated. A schedule for this rehabilitation must be submitted to this office. Your cooperation in this matter is appreciated.

Margie Herrmann

Legal Instruments Examiner

CC:

State Div. OG&M

William A. Ryan - Rocky Mountain Consulting

MAY 3 0 2000

**DIVISION OF** OIL. GAS AND MINING

Form 3160-5 (June 1990)

## **UNITED STATES DEPARTMENT OF THE INTERIOR**

SUBMIT IN TRIPLICATE\* (Other Instructions on reverse side)

Form Approved. Budget Bureau No. 1004-0135 Expires: March 31, 1993

	BUREAU OF LAN	ND MANAGEMENT		5. LEASE DESIGNATION AND SERIAL NO. UTU-65356
Do not use t	his form for proposals to dr	AND REPORTS ON WELLS ill or to deepen or reentry to a differe	ent reservoir.	6. IF INDIAN, ALLOTEE OR TRIBE NAME
	Use "APPLICATION FO	OR PERMIT—" for such proposals		
	SUBMIT	IN TRIPLICATE		7. IF UNIT OR CA, AGREEMENT DESIGNATION
1. TYPE OF WELL OIL GAS	*	SINGLE	MULTIPLE	8. WELL NAME and No.
WELL WEL	C 20	ZONE	ZONE	Federal No. L 44-31
2. NAME OF OPERATOR  Lone Mounta 3. ADDRESS OF OPERATOR	n Production Company			9. API WELL NO. 43-047-33261
P. O. Box 3394	l, Billings, Montana 5916	03 (406) 245-5077		10. Field and Pool, or Exploratory Area
4. LOCATION OF WELL (Foot 623' FSL, 964	age, Sec, T., R., M., or Survey Descrip FEL Section 31-T11S-R	ption)	ECFINEL	) 11. County or Parish, State Uintah County, Utah
(SENW)	-		EC 2 1 2000	
2 CHECK APP	ROPRIATE BOX(s) TO	O INDICATE NATURE OF N	OTICE, REPORT	, OR OTHER DATA
TYPE OF SU	JBMISSION		TYPE OF ACTION	
Notice of Intent		Abandonment		Change of Plans
		Recompletion	*	New Construction
Subsequent Rep	ort	Plugging Back		Non-Routine Fracturing
		Casing Repair		Water Shut-Off
Final Abandonn	ient Notice	Altering Casing		Conversion to Injection
		Other APD Exte	ension ension	Dispose of Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form)
If additiona	l information is needed	d please contact the following:  Dave Koval		
		White River Resource	<b>25</b>	
		Phone: (303) 628-195	1	
S	EE			
18 1	HMENT	· DE	NIED	
4. I hereby certify that the	e foregoing is true and correc	ot.		
igned:	s-Konta	Title: President	D	Date: December 15, 2000
This space for Feder	al or State office use)			
APPROVED BY:	200	TITLE: Petroleum	Engineer	
CONDITIONS OF APPRO	<u> </u>		-	DATE: 01 (19/01
	OVAL IF ANY			DATE: 01 / 19/01
itle 18 U.S.C. Section	1001, make it a crime for	any person knowingly and willfully	to make any departr	DATE: OI / 19/01
alse, fictitious or fraud	1001, make it a crime for		to make any departr jurisdiction.	The sale and come


# Lone Mountain Production Co. APD Extension

Well: Federal R 44-31 Location: SENW Sec. 31, T11S, R22 E

Lease: UTU 65356

Our records show that original APD for this well was rescinded on October 1, 1999 prior to approval. Since it was never approved, an extension can not be granted.

If you have any other questions concerning this matter, please contact Kirk Fleetwood or Ed Forsman of this office at (435) 781-4400.



JAN 29 2001

DIVISION OF CIL, G. ... AND MINING